

MULTIMEDIA PROJECTORS



FullHD Multimedia Projector for the Office

FullHD projection at the office thanks to the Vivitek D912HD, which delivers high brightness level of 3500 ANSI Lumens and a 5000:1 contrast ratio, excellent values for a multimedia projector. The Vivitek D912HD displays impressive color reproduction and amazing performance with the assistance of DLP® and BrilliantColor™ technologies. A stylish projector with a built-in speaker and an assortment of connectivity options, the D912HD is the ultimate match for today's high-definition presentations.

Features

- 3500 ANSI Lumens of brightness with a 5000:1 contrast ratio
- DLP[®] and BrilliantColor[™] technologies from Texas Instruments
- Connectivity options include: HDMI, DisplayPort, VGA-in (2x), VGA-Out, composite video, component video, Svideo
- Network-ready for integration and system administration via RJ45
- Direct 3D over HDMI
- Top-loading, sliding cover for quick and easy lamp replacement
- Keypad lock prevents accidental system adjustments



Specifications	
Brightness	3500 ANSI Lumens
Native Resolution	1080p (1920 x 1080)
Max. Resolution	WUXGA (1920 x 1200) @60Hz
Contrast Ratio	5000:1
Lamp Life and Type	3,000/4,000 Hours (Normal/Eco Mode), 280W/245W
Display Type	Single 0.65" DLP® Technology by Texas Instruments
Throw Ratio	1.58 to 1.92:1 (Distance/Width)
Image Size (Diagonal)	23.5" to 300"
Projection Distance	1.0 to 10.0 m
Projection Lens	F=2.51~2.77, f = 23.5~28.2mm
Zoom Ratio	1.2x
Aspect Ratio	16:9 Native, 4:3, 16:10 Compatible
Offset (full image height)	115%
Keystone Correction	±40º Vertical
Speaker	10 Watt
Remote Control	Fully Featured IR Remote with Laser Pointer
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service)
Security	Kensington [®] Lock Port, Security Bar
Weight	3.15Kg
Dimensions (W x D x H)	285 x 261 x 122 mm
Noise Level	39dB/37dB (Normal/Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 350W/290W (Normal./Eco Mode) <0.5W (Standby Mode)
Warranty	3-Year Warranty, 1-Year or 1,000h Lamp Warranty
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	



marene.

·O,