

## Amp Box S Mono

### Mono power amplifier

- Ultra compact & audiophile
- **NEW!** Advanced amplifier modules
- **NEW!** 2 ohms drive capability
- **NEW!** More power and further improved performance
- Mono input with loop-out (RCA)
- Gold-plated speaker sockets
- Suitable for Banana/Spade/Pin/bare wire
- Trigger input with output for further Amp Box Mono S
- Metal casing protects against vibration and interference
- On/Off switch front-sided
- Faceplate silver or black

#### Technical data

Power output	1 x 40W / 60W @ 8 / 4 ohms 2 ohms drive capability
Frequency response	5Hz - 20kHz (+ 0dB, - 0,5dB)
Signal-to-noise ratio	> -100dB (IEC -A)
THD	< 0,05% @ 10W
Gain	22dB
Input & loop-out	RCA sockets
Sensitivity	1V
Input impedance	47kohm
Speaker sockets	4mm Ø Banana, spade, pin or bare wire
Trigger 12V DC	In&Out, 2-pole jack socket Ø 2,5mm
Power supply	24V/3A DC (peak 7A DC); 100 - 240V, 50/60Hz
Standby power consumption	< 1 Watt
dimensions W x H x D	103 x 36 x 104 (122mm with sockets)
Weight	670g without power supply



### Ultra compact power amplifier - efficient & audiophile!

A ultra high-efficiency Bi-Phase PWM(Pulse Wave Modulation) circuit with SMD parts incorporates 35 years of R&D and gives outstanding audio performance, while staying cool on the outside. It fulfills our demand for high resolution with superior micro dynamics and room-filling power. Sound quality is aimed to be as close as possible to Class A tube amplifiers with their liquid and lifelike presentation. The Amp Box S Mono is micro-sized and therefore allows easy placement and can be switched on & off remotely via a trigger signal. A 45cm power-on cable is supplied for this purpose. For Bi - or Tri-amplification use, the remote power-on signal can be relayed to further units.



< Front view  
(black faceplate)

rear view >

#### connections

